



Caché MV Terminal Independence

Version 2008.1
29 January 2008

Caché MV Terminal Independence
Caché Version 2008.1 29 January 2008
Copyright © 2008 InterSystems Corporation
All rights reserved.

This book was assembled and formatted in Adobe Page Description Format (PDF) using tools and information from the following sources: Sun Microsystems, RenderX, Inc., Adobe Systems, and the World Wide Web Consortium at www.w3c.org. The primary document development tools were special-purpose XML-processing applications built by InterSystems using Caché and Java.



Caché WEBLINK, Distributed Cache Protocol, M/SQL, N/NET, and M/PACT are registered trademarks of InterSystems Corporation.



InterSystems Jalapeño Technology, Enterprise Cache Protocol, ECP, and InterSystems Zen are trademarks of InterSystems Corporation.

All other brand or product names used herein are trademarks or registered trademarks of their respective companies or organizations.

This document contains trade secret and confidential information which is the property of InterSystems Corporation, One Memorial Drive, Cambridge, MA 02142, or its affiliates, and is furnished for the sole purpose of the operation and maintenance of the products of InterSystems Corporation. No part of this publication is to be used for any other purpose, and this publication is not to be reproduced, copied, disclosed, transmitted, stored in a retrieval system or translated into any human or computer language, in any form, by any means, in whole or in part, without the express prior written consent of InterSystems Corporation.

The copying, use and disposition of this document and the software programs described herein is prohibited except to the limited extent set forth in the standard software license agreement(s) of InterSystems Corporation covering such programs and related documentation. InterSystems Corporation makes no representations and warranties concerning such software programs other than those set forth in such standard software license agreement(s). In addition, the liability of InterSystems Corporation for any losses or damages relating to or arising out of the use of such software programs is limited in the manner set forth in such standard software license agreement(s).

THE FOREGOING IS A GENERAL SUMMARY OF THE RESTRICTIONS AND LIMITATIONS IMPOSED BY INTERSYSTEMS CORPORATION ON THE USE OF, AND LIABILITY ARISING FROM, ITS COMPUTER SOFTWARE. FOR COMPLETE INFORMATION REFERENCE SHOULD BE MADE TO THE STANDARD SOFTWARE LICENSE AGREEMENT(S) OF INTERSYSTEMS CORPORATION, COPIES OF WHICH WILL BE MADE AVAILABLE UPON REQUEST.

InterSystems Corporation disclaims responsibility for errors which may appear in this document, and it reserves the right, in its sole discretion and without notice, to make substitutions and modifications in the products and practices described in this document.

For Support questions about any InterSystems products, contact:

InterSystems Worldwide Customer Support

Tel: +1 617 621-0700
Fax: +1 617 374-9391
Email: support@InterSystems.com

Table of Contents

Introduction	1
1 Terminal Definition	3
1.1 The TERMDEFS File	3
1.2 Adding A New Terminal Definition	4
1.3 Modifying An Existing Terminal Definition	5
1.4 The COMPILE.TERM Command	5
1.5 The Default Terminal Type	5
1.6 The TERM Environment Variable	5
1.7 Supported TERMINFO Manipulation Codes	6
2 Terminal Output	9
2.1 TERM Command	9
2.2 The CHOOSE.TERM Command	10
2.3 The SYSTEM() Function	10
2.4 The @() Function	11
2.5 Pre-Defined Names	11
2.6 jBASE- And Reality-specific Codes	15
3 Terminal Input	17
3.1 The KEYS command	17
3.2 Keyboard independence	17

Introduction

Terminal and keyboard independence refers to the ability of an application to communicate with a user's output device (terminal) and input device (keyboard) without regard to the manufacturer of the device. The control sequences required to manipulate various aspects of the output device (e.g. move cursor, add bold, underscore etc.) varies among manufacturers. Similarly, the sequence of characters generated by a keyboard when certain non-alpha keys are depressed (for example, the function keys, cursor up key etc.) also varies. For MultiValue applications, help exists from the language to provide independence of this variance among devices.

In the domain of this discussion, "terminal" refers to console windows such as Caché Terminal sessions, and the Microsoft Windows command terminal, and to legacy "green screen" terminals such as the VT-100 or the Wyse 60.

Caché contains set of terminal definitions suitable for Multi Value applications. For practical purposes, this is limited to the most popular definitions, but it is easy to add or modify existing definitions. These MultiValue definitions differ from the terminal definitions of standard Caché devices because the latter do not cover all the requirements of a MultiValue application. The MV definitions pointed to by the TERMDEFS definition in the VOC. The layout of an entry in the TERMDEFS file is a simple text record which mirrors the terminal definition given by the "infocmp" command on most Unix systems.

When a user begins a MultiValue session, Caché defaults to use a terminal of type CACHE of fixed screen size. This can be modified by executing the TERM command, as detailed later.

The application can write control characteristics to the terminal in an independent way using the MultiValue @() function.

There is no real MultiValue standard for reading control characteristics from the keyboard. Pressing the F1 key on a keyboard, for example, will simply return a stream of regular characters in the range \$c(32) through \$c(255). Examples of input processing are also available in the SAMPLES database.

Note: These facilities allow replacement of the jBASE CommandInit and CommandNext subroutines.

1

Terminal Definition

1.1 The TERMDEFS File

Each account (namespace) in MultiValue will have an F pointer in the VOC called TERMDEFS which points to a database-wide file, ^%MV.TERMDEFS. Each entry in this global contains a simple text file which defines the characteristics of a terminal (both output and input characteristics). The global node name should be upper case.

The layout of these text files is one or more lines, delimited by CR, CR/LF or @AM (\$C(254)). The lines have the same attributes as that presented by the "terminfo" command available on most Unix systems. Indeed many of the supplied terminal definitions will come from Unix declarations. For example, the global ^%MV.TERMDEFS("VT100") might look like this:

```
#
vt100|vt100-s|dec vt100 (w/advanced video),
am, msgr, xenl, xon,
cols#80, it#8, lines#24, vt#3,
acsc=`aaffggjjkkllmmnnoopppqrrssttuuvvwwxxyyzz{{||}}~~,
bel=^G, blink=\E[5m$<2>, bold=\E[1m$<2>,
clear=\E[H\E[J$<50>, cr=^M, csr=\E[%i%p1%d;%p2%dr,
cub=\E[%p1%dD, cub1=^H, cud=\E[%p1%dB, cud1=^J,
cuf=\E[%p1%uC, cuf1=\E[C$<2>,
cup=\E[%i%p1%d;%p2%dH$<5>, cuu=\E[%p1%dA,
cuul=\E[A$<2>, ed=\E[J$<50>, el=\E[K$<3>, ell=\E[lK$<3>,
enacs=\E(B\E)0, home=\E[H, ht=^I, hts=\EH, ind=^J, kal=\EOq,
ka3=\EOs, kb2=\EOr, kbs=^H, kcl=\EOp, kc3=\EOn, kcub1=\EOD,
kcud1=\EOB, kcufl=\EOC, kcuul=\EOA, kent=\EOM, kf0=\EOy,
kf1=\EOP, kf10=\EOx, kf2=\EOQ, kf3=\EOR, kf4=\EOS, kf5=\EOt,
kf6=\EOu, kf7=\EOv, kf8=\EOl, kf9=\EOw, rc=\E8,
rev=\E[7m$<2>, ri=\EM$<5>, rmacs=^O, rmam=\E[?7l,
rmkx=\E[?1l\E>, rmso=\E[m$<2>, rmul=\E[m$<2>,
rs2=\E>\E[?31\E[?41\E[?51\E[?7h\E[?8h, sc=\E7,
sgr=\E[0%?%p1%p6%|%t;1%:%?%p2%t;4%:%?%p1%p3%|%t;7%:%?%p4%t;5%:;%?%p9%t\016%e\017%;$<2>,
```

```
sgr0=\E[m\017$<2>, smacs=^N, smam=\E[?7h, smkx=\E[?1h\E=,  
smso=\E[7m$<2>, smu1=\E[4m$<2>, tbc=\E[3g,
```

In fact, this example was taken from a UNIX definition of a vt100 terminal. It shows all the characteristics of the terminal. Not all of these are needed by Caché and those that are not relevant will be ignored. This makes importing terminal definitions relatively painless since no editing is required.

The pad characters, denoted by \$<nn>, are for really really old terminals and hark from the days before flow control to serial devices. This information is ignored.

In the above example, \E denotes the escape character, %c(27), non-displayable characters denoted by ^A through ^Z being %c(1) through %c(26). If a string is not a constant and requires parameters to determine the eventual string, for example moving the cursor to a particular row and column, these are denoted by % as described in the **terminfo** manual pages on a UNIX system.

The first line shown in the example is a comment. The second line is set of fields delimited by the | character, the last field simply being a description, the other fields being the name of the terminals this defines. This allows synonym terminals to be defined by the same source. Hence a single source in the TERMDEFS file may create one or more compiled entries in the TERMCMP file.

1.2 Adding A New Terminal Definition

Create the source definition for the terminal. Caché uses a standard source as output by the "infocmp" command on UNIX systems. Therefore, the usual way of adding a new terminal definition, assuming it already works on a UNIX system, as follows:

- Create a source file on a UNIX system, for example with the command,

```
infocmp wyse50 > /tmp/wyse50def
```
- Copy this source file to a folder/directory on your target system, for example, to

```
C:\tmp\wyse50def.txt
```
- Copy this file into the TERMDEFS file, cut-and-paste with ED to add an entry into the TERMDEFS file
- Run the COMPILE.TERM

Note: The item id of the item in the TERMDEFS file is uppercase and is the name of the terminal type. The name **MUST** be uppercase, although when you refer to the terminal type with the TERM command it is case insensitive.

1.3 Modifying An Existing Terminal Definition

A developer may use the ED command to edit an existing entry in the TERMDEFS file and then run the COMPILE.TERM command.

1.4 The COMPILE.TERM Command

The data for terminal definitions exists in 2 globals. The %MV.TERMDEFS global contains the source for the definition. The %MV.TERMCMP global contains the compiled definition used by the run-time. To compile the sources from %MV.TERMDEFS to the compiled version in %MV.TERMCMP issue the COMPILE.TERM command. This command takes no arguments -- it simply compiles all the definitions in the %MV.TERMDEFS file. For example,

```
USER: COMPILE.TERM
123 terminal definitions compiled
USER:
```

1.5 The Default Terminal Type

By default, the type of a terminal is CACHE. Users can change the default via the TERM command, for example,

```
USER: TERM vt100
USER: ; PRINT SYSTEM(7)
vt100
USER: TERM VT100
USER: ; PRINT SYSTEM(7)
VT100
```

Note: The case of the terminal name typed is preserved.

1.6 The TERM Environment Variable

The **TERM** command also sets the TERM environment variable. When MV starts, if the terminal specified cannot be loaded, the MV shell will

1. Display an error message to that effect;

2. Attempt to load the terminal type, CACHE;
3. If successful, display a message that the terminal type is set to CACHE. If unsuccessful (because, for example, it has been removed from the TERMDEFS file), the terminal type will be set to UNKNOWN and an error message indicating this will be displayed instead.

1.7 Supported TERMINFO Manipulation Codes

Cursor addressing and other strings requiring parameters are described by a parameterized string capability. For example, to address the cursor, the “cup” capability is supported. It expects using two parameters: the row and column to move the cursor to. (For more info, see the UNIX terminfo(5) man page.

This parameter mechanism uses a stack and special % codes to manipulate it. Typically, a sequence may push one or more parameters onto the stack and manipulate them in some way. The Caché termdefs file supports the following subset of the UNIX capability:

Code	Description
One or more digits	Push the integer onto the stack
%%	Add “%” to the output string
%p[1-9]	Push the designated parameter onto the stack
%c	Pop an integer from the stack and append it to the output string as a character
%d	Pop an integer from the stack and print its decimal value to the output string
%i	Add 1 to the first two parameters (p1 and p2)
%F	Equivalent to “%p1%d” (Caché extension)
%G	Equivalent to “%p2%d” (Caché extension)
%H	Equivalent to “%p1%d;%p2%d” (Caché extension)
\x'	Push the character represented by the escape sequence onto the stack (the representation is given in octal)
%+, %-, %/, %*, %m	Arithmetic operations on the top two positions of the stack: addition, subtraction, division, multiplication, and modulo, respectively.

Let us assume we want to move the cursor to column 3 , row 6 (column and row numbers start at 0, so column 3 is actually the 4th column and row 6 is the 7th row). The cursor function will be called with 2 parameters, 3 and 6, and the string

```
cup=\E[%i%p2%d;%p1%dH$<5>
```

is interpreted as follows:

Code	Interpretation
\E	Append the ESCape character (\$CHAR(27)) to the output string
[Append the character, “[”, to the output string
<i>%i</i>	Add 1 to the first two parameters; 3 and 6 become 4 and 7, respectively
<i>%p2</i>	Push parameter 2 (a 7) onto the stack
<i>%d</i>	Print the top of the stack to the output string
;	Append the character, “;”, to the output string
<i>%p1</i>	Push parameter 1 (a 4) onto the stack
<i>%d</i>	Print the top of the stack to the output string
H	Append the character, “H”, to the output string
\$<5>	Add 5 units of pad character. Caché ignores this sequence. It was used for very old character-oriented terminals running over an asynchronous link without flow control.

So the resulting control sequence sent to the terminal to move the cursor to column 3, row 6 (zero-based) consists of the ESCape character followed by the characters “[7;4H” .

2

Terminal Output

2.1 TERM Command

The **TERM** command allows a user to query or establish certain characteristics of the terminal. When used from the shell as an interactive command:

```
TERM
```

the command displays the terminal characteristics. The terminal “type” can also be set from the command line, for example,

```
TERM VT220
```

sets the terminal to have the characteristics of a DEC VT220.

The characteristics of the terminal are usually set from a program, however, where the command format is

```
TERM swidth,sdepth,,,,pwidth,pdepth,termtype
```

where:

- *swidth* and *sdepth* are the screen width (in characters) and depth (in lines)
- *pwidth* and *pdepth* are the printer width and depth (also in characters and lines, respectively)
- *termtype* is the terminal type identifier and can appear anywhere in the command as a non-numeric argument

Note: Arguments 3 through 6 of the command are no longer used; if present, they will be ignored.

The **TERM** command also supports single character terminal names which are synonyms for other terminal names. For example,

```
TERM W
```

selects the Wyse 60 terminal. To see a list of terminals supported and their single character synonym (if any), see the **CHOOSE.TERM** command.

2.2 The CHOOSE.TERM Command

The **CHOOSE.TERM** command allows you to see what terminals are supported on your system and then allows you to select a terminal type by entering a number, the name, or the short name. For example,

```
USER:CHOOSE.TERM
```

Terminal Description	Term Name	Short Name
-----	-----	-----
1) ansi/pc-term compatible with co	ANSI	
2) AT&T 605 80 column 102key keybo	ATT605	Z
3) cache terminal based on vt220	CACHE	
4) Hazeltine Esprit I,	ESPRIT	E
...		
...		
...		
31) xterm terminal emulator (X Wind	XTERM	

Choose number, term name or short name :

The Short Name field is where the terminal definition has a “termtype=Xentry” and so allows the terminal to be selected via the **TERM** command and using a single character synonym.

2.3 The SYSTEM() Function

This function is used to return a limited set of information about the terminal in use. The format is

```
SYSTEM(<selector>)
```

where <selector> identifies the information desired. The allowed values for <selector> are:

- 1: return a non-zero value is output is not directed to a terminal

- 2: returns the screen width
- 3: returns the screen depth
- 7: returns the type name of this terminal

2.4 The @() Function

Multi Value BASIC provides terminal output independence using the @() function call as follows:

- @(*m*,*n*) where *m* is a positive value
Moves the cursor to column *m* and row *n*, where @(0,0) is the top left hand side of a terminal.
- @(*m*) where *m* is a positive value
Moves the cursor to column *m* on the current row.
- @(*m*) where *m* is negative value
Generates video effect character strings. The value of *m* and the effect intended are emulation dependent and given by the table below.
- @(*m*,*n*) where *m* is a negative value
The same as @(*m*), except some video effects take an optional argument , *n*, as shown by (*nn*) in the table below.

2.5 Pre-Defined Names

The table below shows all the values we use from a terminfo definition. Caché does not use them all; only use the ones necessary to support MultiValue Basic. In this table, there are some Caché defined names. These are shown by the name starting with an 'x' and the word "NEW" in the description field.

In the table below, the @(-*nn*) values vary between emulation. The values shown are for Cache Ideal (aka Universe) emulation unless otherwise noted. The expression 'video attributes' refer to effects such as bold, dim, reverse and so on.

Name	Description	Usage
bel	Bell sounds	@(-108) or @(-19) in Unidata emulation
blink	Start blinking video attribute	@(-5)

Name	Description	Usage
bold	Start bold video attribute	@(-58)
civis	Make cursor invisible	@(-31)
clear	Clear screen and move cursor home	@(-1)
cnorm	Turn cursor back on	@(-32)
cub	Move the cursor left a number of columns.	@(-9,nn). @(-9) when cub1 not available
cub1	Move the cursor left a single column	@(-9). @(-9,nn) when cub not available
cud	Move the cursor down a number of rows.	@(-33,nn). @(-33) when cud1 not available
cud1	Move the cursor down a single row	@(-33). @(-33,nn) when cud not available
cuf	Move the cursor right a number of columns	@(-nn) and @(-34,nn). @(-34) when cuf1 not available
cuf1	Move the cursor right a single column.	@(-34). @(n) and @(-34,nn) when cuf not available.
cup	Position the cursor at a specific column and row	@(-nn,m) function calls
cuu	Move the cursor up a number of rows.	@(-10,nn). @(-10) when cuu1 not available
cuu1	Move the cursor up a single row	@(-10). @(-10,nn) when cuu not available
dch	Delete a number of characters	@(-22,nn). @(-22) when dch1 not available
dch1	Delete one character	@(-22) . @(-22,nn) when dch not available
dim	Start dimmed mode attribute	@(-11)
dl	Delete a number of lines	@(-18,nn). @(-18) when dl1 not available
dl1	Delete one line	@(-18) . @(-18,nn) when dl not available

Name	Description	Usage
ech	Erase a number of characters	@(-71,nn)
ed	Clear screen from cursor to end of screen	@(-3)
el	Clear screen from cursor to end of line	@(-4)
home	Move cursor to home position	@(-2)
hpa	Set column position	@(-70,nn). @(-70) if hpa1 not available
ich	Insert a number of characters	@(-19,nn). @(-19) when ich1 not available
ich1	Insert one character	@(-19) . @(-19,nn) when ich not available
il	Insert a number of lines	@(-17,nn). @(-17) when il1 not available
il1	Insert one line	@(-17) . @(-17,nn) when il not available
ind	Scroll up a single lines	@(-48). @(-48,nn) when indn not available
indn	Scroll up a number of lines.	@(-48,nn). @(-48) when ind not available
mc0	Dump contents of screen to printer	@(-28)
mc4	Reset auxilliary printing	@(-24). @(-26) if xmc4i not available
mc5	Start auxilliary printing to screen and printer	@(-23). @(-25) if xmc5i not available
prot	Start protected field attribute	@(-7)
rev	Start reverse video attribute	@(-13)
ri	Scroll up a single line	@(-49). @(-49,nn) when rin not available
rin	Scroll up a number of lines.	@(-49,nn). @(-49) when ri not available

Name	Description	Usage
rmir	Reset insert mode	@(-21)
rmso	Exit standout attribute	@(-59)
rmul	Reset underscore attribute	@(-16)
setab	Set a background colour	@(-38) and @(-38,nn)
setaf	Set a foreground colour	@(-37) and @(-37,nn)
sgr	Reset specific video attributes Bit mapped video attribute calls. sgr0 Reset all video attributes	@(-128) function call. When other reset attributes not found
smir	Start insert mode	@(-20)
smul	Start underscore attribute	@(-15)
xblink	NEW Reset blinking video attribute	@(-6)
xbold	NEW Reset bold video attribute	@(-59) if rmso is not available
xdim	NEW Reset dimmed mode attribute	@(-12)
xdisableprotect	Disable protected field handling	@(-63) or @(-12) in D3 mode
xdmi	NEW Disable manual input	@(-42)
xemi	NEW Enable manual input	@(-43)
xenableprotect	Enable protected field handling	@(-62) or @(-11) in D3 mode
xenter132	NEW Enter 132 column mode	@(-30)
xenter80	NEW Enter 80 column mode	@(-29)
xhpa1	NEW Set column position	@(-70). @(-70,nn) if hpa not available
xmc4i	NEW Reset auxilliary printing to printer only	@(-26)
xmc5i	NEW Start auxilliary printing to printer only	@(-25)

Name	Description	Usage
xprot	NEW Reset protected field attribute	@(-8)
xrev	NEW Reset reverse video attribute	@(-14)
xrnumeric	NEW Reset numeric keypad	@(-57)
xrtrunc	NEW Reset line truncate	@(-55)
xscl	NEW Scroll left a single column	@(-51). @(-51,nn) when xscl1 not available
xscl1	NEW Scroll left a number of columns.	@(-51,nn). @(-51) when xscl not available
xscr	NEW Scroll right a single column	@(-50). @(-50,nn) when xscr1 not available
xscr1	NEW Scroll right a number of columns.	@(-50,nn). @(-50) when xscr not available
xsetafdim	NEW Set foreground colour dimmed	@(-109 through @(-116) or @(-57) to @(-64) in D3 emulation
xsmul	NEW Reset underscore attribute	@(-16) if rmul is not available
xsnumeric	NEW Set numeric keypad	@(-56)
xstrunc	NEW Set line truncate	@(-54)

2.6 jBASE- And Reality-specific Codes

Values -128 through -191 are for Reality video effects and are a bit map of video effects as shown in the list below. Caché supports these values for ALL emulations as there is no conflict. These values are additive. The only value Cache, supports is:

- 0x01 – Half intensity
- 0x02 – Blink
- 0x04 – Reverse
- 0x08 – Blanked

Terminal Output

- 0x10 – Underscore
- 0x20 – Bold
- 0x40 – (not defined)
- 0x80 – Always 1

Note: Value @(-128), which turns off ALL video effects, is available for all emulations.

3

Terminal Input

3.1 The KEYS command

This is a simple command that allows the user to see what characters are returned from the keyboard after depressing a particular key. The input will therefore be 100% binary and all characters will be interpreted by the KEYS command. Because of the manner of executing this command, there cannot be a "quit program" keystroke, instead the command will terminate after 10 seconds of inactivity.

This KEYS command is very useful when "debugging" a terminal definition. For example, to see what keystroke function key 3 generates, issue the KEYS command, depress function key 3, and then wait 10 seconds for the KEYS program to terminate. For example, the following example shows that, on this terminal, hitting F3 will generate an escape character followed by ascii "O" and then ascii "R".

```
USER: KEYS
This program terminates after 10 seconds of inactivity.
Key: esc          0x1b 0033
Key: O            0x4f 0117
Key: R            0x52 0122
key: Timeout
USER:
```

3.2 Keyboard independence

jBASE provides a pair of supplied subroutines called **CommandInit** and **CommandNext**. These subroutines are supplied in the dev/mv/samples directory supplied with Caché. Also included in the samples directory is file CommandInclude which is a replacement for the jCmdKeys.h file used in jBASE keyboard independence. This source defines values such as cmd_cursor_up which a jBASE

application will probably be using. The values specified in Caché are different from jBase, but the end result is the same. This mechanism is available for all emulations, not just jBASE.

Note: For jBASE releases 4.1 and higher, these subroutines were renamed JBASECommandInit and JBASECommandNext, so depending upon which release of jBASE you are porting from, you might need to rename these subroutines in our samples directory.

To use these samples, you can copy them to your own source file and compile and catalog them. The following selection shows an example of creating a MV file called COMMANDBP which points directly to the samples themselves. This is used to compile and catalog the source code directly from the samples directory, and then run a small example program to show the installation has worked. The example can also be copied to a local file and run from there.

```
USER:ED VOC COMMANDBP
COMMANDBP
New record.
----:I
0001= F
0002= C:\InterSystems\CacheSysBuild282\dev\mv\samples
0003= C:\InterSystems\CacheSysBuild282\dev\mv\samples
0004=
Bottom at line 3.
----:FI
"COMMANDBP" filed in file "VOC".
USER:BASIC COMMANDBP CommandInit CommandNext CommandExample
CommandInit
[B0] Compilation completed.
CommandNext
[B0] Compilation completed.
CommandExample
[B0] Compilation completed.
USER:CATALOG COMMANDBP CommandInit CommandNext CommandExample
[243] 'CommandInit' Cataloged Local.
[243] 'CommandNext' Cataloged Local.
[243] 'CommandExample' Cataloged Local.
USER:CommandExample
Function key 2 pressed
Function key 3 pressed
cmd returned was '2'
Timeout after 5 seconds
Alpha character returned, value = 'x'
USER:
```